

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A welding system characterized in that a welding device in which a reciprocating movable electrode is attached to moving drive means, the movable electrode and a fixed electrode forming a pair, and a part feeding device for feeding a part to a target position by a feeding rod moving forward and backward are coupled to one another through ~~[[a]]~~ an elongated coupling member, so that an end position of the feeding rod moved forward and an end portion of the movable electrode or the fixed electrode are in a predetermined relative positional relation;

wherein a fixing member for fixing the welding device on a stationary member is provided; and

wherein:

the fixing member comprises a member main body and a fixed shaft member which are coupled to each other;

the member main body is coupled to an end portion of the moving drive means;

the elongated coupling member is fixed to the member main body, and the part feeding device is fixed to the elongated coupling member;

the fixed shaft member is coupled to the stationary member to fix the welding ~~system~~ device on the stationary member;

an axis line of the fixed shaft member is approximately coaxial with a moving axis line of the movable electrode; and

a rotational position of the welding system can selectively be set by rotating the member main body with respect to the fixed shaft member.

2. (canceled)

3. (canceled)
4. (previously presented) The welding system according to claim 1, wherein the coupling member is integrated with the fixing member.
5. (previously presented) The welding system according to claim 1, wherein a plurality of part feeding devices each of which feeds a different type of part are attached to the coupling member or an auxiliary member integrated with the coupling member.
6. (previously presented) The welding system according to claim 1, wherein the part is a projection bolt with a flange which is provided with a projection for welding.
7. (previously presented) The welding system according to claim 1, wherein the part is a projection nut provided with a projection for welding.
8. (previously presented) The welding system according to claim 1, wherein a support rod which is attached to the part feeding device and extends approximately in a vertical direction penetrates a clamp block fixed on the stationary member and the clamp block clamps and loosens the outer periphery of the support rod to set the vertical position of the support rod, and an auxiliary clamp block for setting a moving distance of the support rod in advance is disposed over or under the clamp block in such a manner that the auxiliary clamp block penetrates the support rod.
9. (previously presented) The welding system according to claim 8, wherein the clamp block has a penetration hole through which the support rod with a circular cross section penetrates, a slit section continued from the penetration hole, and a fixing bolt penetrating the slit section.

10. (previously presented) The welding system according to claim 8, wherein: the auxiliary clamp block has a penetration hole through which the support rod penetrates, a slit section continued from the penetration hole, and a fixing bolt penetrating the slit section; and an end face of the auxiliary clamp block can abut to an end face of the clamp block.

11. (previously presented) The welding system according to claim 8, wherein the part feeding device is a device that feeds a part held by the feeding rod to the fixed electrode or the movable electrode of the welding device, in order to weld the part fed between the fixed electrode and the movable electrode by the feeding rod to a target position.

12. (previously presented) A positioning device of a part feeding device wherein a support rod which is attached to the part feeding device and extends approximately in a vertical direction penetrates a clamp block fixed on a stationary member and the clamp block clamps and loosens the outer periphery of the support rod to set the vertical position of the support rod, characterized in that an auxiliary clamp block for setting a moving distance of the support rod in advance is disposed over or under the clamp block in such a manner that the auxiliary clamp block penetrates the support rod.

13. (previously presented) The positioning device of the part feeding device according to claim 12, wherein the clamp block has a penetration hole through which the support rod with a circular cross section penetrates, a slit section continued from the penetration hole, and a fixing bolt penetrating the slit section.

14. (previously presented) The positioning device of the part feeding device according to claim 12, wherein:

the auxiliary clamp block has a penetration hole through which the support rod penetrates, a slit section continued from the penetration hole, and a fixing bolt

penetrating the slit section; and an end face of the auxiliary clamp block can abut to an end face of the clamp block.

15. (previously presented) The positioning device of the part feeding device according to claim 12, wherein the part feeding device is a device that feeds a part held by a feeding rod to a fixed electrode or a movable electrode of a welding device, in order to weld a part fed between the fixed electrode and the movable electrode by the feeding rod to a target position.